



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® PRESTO PATCH™ Drywall Plug Wall Repair Patch

PRODUCT DESCRIPTION

DAP® Presto Patch™ is a simple, structural and invisible solution for permanently and easily repairing holes in drywall. This product repairs up to 4" holes in standard ½" drywall. Presto Patch includes one pre-cut drywall circle with oversized taping paper attached, a foam template and step-by-step instructions.



PACKAGING	COLOR	UPC
4" Patch	Neutral	7079809151

KEY FEATURES & BENEFITS

- Permanent drywall repair
- Restores structural integrity of wall
- Makes repairs invisible
- Time saving solution
- Pre-cut for easy installation
- Porous drywall paper for permanent repair

SUGGESTED USES

For use with standard drywall. Not for use with lath or plaster. Do not install DAP Presto Patch in temperatures below 45°F (7°C) or above 85°F (30°C).

APPLICATION

Suggested Additional Supplies: ± ½ pint of joint compound (not spackling), drywall saw, 6" putty knife, medium and fine sandpaper, and pencil.

1. Center the foam template provided around the damaged area and trace the circle.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

2. With a drywall saw, cut along the outside of traced circle. Do not cut deeper than the 1/2" drywall patch, to avoid any electric, gas, plumbing or framing behind the wall.
3. Test fit Presto Patch in the hole and enlarge the hole if necessary.
4. Lay Presto Patch paper side down and apply generous amount of joint compound on the paper and along edge of drywall circle.
5. Insert Presto Patch into hole, being careful not to push through the wall.
6. Use a putty knife from center of the plug and squeeze the excess joint compound toward the outer edges.
7. Once paper is flat on the surface, apply a generous amount of compound and spread into a thin layer covering the entire patch. Let compound dry as recommended by manufacturer.
8. Sand using medium grit and finish with fine, then prime and paint.

NOTE: Paper may wrinkle but flattens when dry.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

- Material: 1/2" thick drywall with a 3 7/8" diameter and porous drywall paper.
- Shelf Life: unlimited if kept dry (keeping away from high humidity)

CLEAN UP & STORAGE

Wash hands and tools with warm soap and water. Dry joint compound must be sanded or scraped away.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com